


WWW.HUIYE.COM

BIKE COMPUTER BROCHURE 2023

BIKE COMPUTER SUPPLIER

HUIYE is a supplier of bike computers and IoT solutions integrating R&D, manufacture, and sales. We meet the needs of every customer around the world with professional service capabilities and provide customers with safe, reliable, and high-quality Bike Computers, GPS trackers, IoT products, and solutions. Today, they have been widely used in the IoT industries such as E-Bike, E-Scooter, E-Motorcycle, Vehicle transportation, Fleet management, Asset tracking, Safety management, and Sharing economy.



HUIYE BIKE COMPUTER APP-BIKEGO

HUIYE Bike Computers, which can be used in E-Bike, E-Scooter and E-Motorcycle, provide riders with cycling data, cycling speed, ebike management, ebike status monitoring, bluetooth unlock, projected navigation, call reminder and other functions. HUIYE bike computer is available in a choice of languages and themes, or you can customize it. At the same time, HUIYE bike computer can connect to mobile APP, check cycling data and manage ebike, making every ride better and smarter.


Display Items

- Current Speed
- Max Speed
- Average Speed
- Single Mileage
- Total Mileage
- Remaining Mileage
- Error Code
- Battery Capacity
- Power-aided Shoving


Parameters Setup

- Backlight Brightness
- Unit Switch
- Speed Limit
- Wheel Diameter
- Battery Voltage Switch
- Sleep Mode Timing
- Data Reset
- Password Setting

English, German, French, Spanish, etc (Customization)



Cycling Date



E-Bike Management




Navigation Settings

(Notes: Mapbox pay for use)



Bluetooth Upgrade

HUIYE Bike Computer APP



BIKEGO

Used in B02N, B03N, B04N, BM02, T01;



Android
Google Play



ISO



BIKEGO+

Used in B06, S402;



Android
Google Play



ISO

Product		B06	S402	B02N	B03N	B04N	BM02	T01	
Picture									
Communication	Network	LTE Cat.1						√	
	Protocol	UART			√				
		CAN				√			
		SIF		√		√	√	√	√
Screen	Size		4"	2.4"	2.8"	3.5"	3.5"	4"	
	Type	LED	LCD		IPS				
	Image Resolution			320*240PX	240*320PX	320*480PX	480*320PX	800*480PX	
	Luminance				> 600 cd/m2				
Operating Voltage		12V/24V/36V/48V/60V							
Holder Diameter(mm)		22.2	22.2/25.4/31.8	22.2/25.4	22.2/25.4/31.8	22.2/25.4/31.8	22.2/25.4/31.8	22.2/25.4	
Separate Remote Control			√		√	√	√	√	
Light	Soft-Switching	√					√		
	Independent Control		√	√	√	√		√	
	Voltage		6V 3W	6V 3W	6V 3W	6V 3W		6V 3W	
Type-C Interface			√*	√*	√*	√*	√	√*	
Ingress Protection Rating		IP67							IP65
Bluetooth		5.2+BLE(Optional)	5.2+BLE(Optional)	4.0+ BLE				5.2+BLE(Optional)	
GPS								√	
Light Sensor			Optional			Optional	Optional	Optional	
Language		English, German, French, Spanish, Portuguese, Russian, Japanese, etc (Customization)							
APP		BIKEGO+			BIKEGO				

*: Choose between light and reverse charging; Don't plug and unplug with electricity, otherwise may damage the electronic control accessories.



LED
Screen



Cycling
Data






E-Bike
Management



Bluetooth
Unlock



BIKEGO+
APP



B06 | UART/CAN

Dimension	Length*Width*Height	26*45*48 (mm)
	Holder Diameter	22.2 (mm)
Screen	Size	17*34 (mm)
	Type	LED
Connector	Type	M5 Waterproof Connector
	Length	20 cm
Other Feature	Bluetooth	5.2 + BLE (Optional)

General Feature	Operating Voltage	12V/24V/36V/48V/60V
	Operating Temperature	-20 °C --+70 °C
	Ingress Protection Rating	IP67
	Weight	28g
	Communication Protocol	UART/CAN
Certification	RoHS	Support Customization



LCD Screen



Cycling Data





E-Bike Management



Bluetooth Unlock



BIKEGO+ APP



B402 | UART/CAN/SIF

Dimension	Length*Width*Height	104.3*62.5*13.95 (mm)
	Holder Diameter	22.2/25.4/31.8 (mm)
Screen	Size	4"
	Type	LCD
	Color	Red/Yellow/Blue/Green/White
Connector	Type	M5 Waterproof Connector
	Length	22 cm

General Feature	Operating Voltage	12V/24V/36V/48V/60V
	Operating Temperature	-20 °C +70 °C
	Ingress Protection Rating	IP67
	Weight	TBD
Other Feature	Communication Protocol	UART/CAN/SIF
	Bluetooth	5.2 + BLE (Optional)
	Type-C Interface	Support*
Certification	RoHS CE FC ISO 13849	Support Customization

*: Choose between lights and reverse charging;



Cycling
Data



E-Bike
Management



Call
Reminder



Projected
Navigation






Bluetooth
Unlock



Language
Customizable



BIKEGO
APP



B02N | UART/CAN

Dimension	Length*Width*Height	86.8*50.5*12.5 (mm)
	Holder Diameter	22.2/25.4 (mm)
Screen	Size	2.4"
	Type	IPS
	Color	RGB
	Image Resolution	320*240PX
Connector	Type	M5 Waterproof Connector
	Length	20 cm

General Feature	Operating Voltage	12V/24V/36V/48V/60V
	Operating Temperature	-20 °C +70 °C
	Ingress Protection Rating	IP67
	Weight	67g
Other Feature	Communication Protocol	UART/CAN
	Bluetooth	4.0 + BLE
	Type-C Interface	Support*
Certification	RoHS CE FC ISO 13849	Support Customization



Cycling Data



E-Bike Management



Call Reminder



Projected Navigation






Bluetooth Unlock



Language Customizable



BIKEGO APP



B03N | UART/CAN/SIF

Dimension	Length*Width*Height	75.5*55.3*9.1 (mm)
	Holder Diameter	22.2/25.4/31.8 (mm)
Screen	Size	2.8"
	Type	IPS
	Color	RGB
	Image Resolution	240*320PX
Connector	Type	M5 Waterproof Connector
	Length	20 cm

General Feature	Operating Voltage	12V/24V/36V/48V/60V
	Operating Temperature	-20 °C ~+70 °C
	Ingress Protection Rating	IP67
	Weight	80g
Other Feature	Communication Protocol	UART/CAN/SIF
	Bluetooth	4.0 + BLE
	Type-C Interface	Support*
Certification	RoHS CE FC	Support Customization

*: Choose between lights and reverse charging;



Cycling
Data



E-Bike
Management



Call
Reminder



Projected
Navigation






Bluetooth
Unlock



Language
Customizable



BIKEGO
APP



B04N | UART/CAN/SIF

Dimension	Length*Width*Height	89.3*60.8*9.1 (mm)
	Holder Diameter	22.2/25.4/31.8 (mm)
Screen	Size	3.5"
	Type	IPS
	Color	RGB
	Image Resolution	320*480PX
Connector	Type	M5 Waterproof Connector
	Length	20 cm

General Feature	Operating Voltage	12V/24V/36V/48V/60V
	Operating Temperature	-20 °C ~+70 °C
	Ingress Protection Rating	IP67
	Weight	92g
Other Feature	Communication Protocol	UART/CAN/SIF
	Bluetooth	4.0 + BLE
	Light Sensor	Optional
Certification	Type-C Interface	Support*
	RoHS CE FC ISO 13849	Support Customization

*: Choose between lights and reverse charging;



Cycling Data



E-Bike Management



Call Reminder



Projected Navigation






Bluetooth Unlock



Language Customizable



BIKEGO APP



BM02 | UART/CAN/SIF

Dimension	Length*Width*Height	120.1*78.3*15.3 (mm)
	Holder Diameter	22.2/25.4/31.8 (mm)
Screen	Size	3.5"
	Type	IPS
	Color	RGB
	Image Resolution	480*320PX
Connector	Type	M5 Waterproof Connector
	Length	20 cm

General Feature	Operating Voltage	12V/24V/36V/48V/60V
	Operating Temperature	-20 °C ~+70 °C
	Ingress Protection Rating	IP67
	Weight	136g
Other Feature	Communication Protocol	UART/CAN/SIF
	Bluetooth	4.0 + BLE
	Light Sensor	Optional
Certification	Type-C Interface	Support
		RoHS CE FC Support Customization



IoT
LTE Cat.1
Network


Cycling
Data


E-Bike
Management





Call
Reminder


GPS
Navigation


Bluetooth
Unlock


Language
Customizable


BIKEGO
APP




T01 | LTE Cat.1/GPS/UART/CAN/SIF

Dimension	Length*Width*Height	122*76.2*16 (mm)
	Holder Diameter	22.2/25.4 (mm)
Screen	Size	4"
	Type	IPS
	Color	RGB
	Image Resolution	800*480PX
Connector	Type	M5 Waterproof Connector
	Length	20 cm
Certification	RoHS CE FC	Support Customization

General Feature	Operating Voltage	12V/24V/36V/48V/60V
	Operating Temperature	-20 °C ~+70 °C
	Ingress Protection Rating	IP65
	Weight	TBD
Communication	Network	LTE Cat.1
	Protocol	UART/CAN/SIF
Other Feature	Bluetooth	5.2 + BLE (Optional)
	GPS	Support
	Light Sensor	Optional
	Type-C Interface	Support*


*: Choose between lights and reverse charging;

HUIYE Remote Control




K31

Length*Width*Height	44.1*43.5*46 (mm)
Holder Diameter	22.2 (mm)
Connector	M5 Waterproof Connector
Ingress Protection Rating	IP67



K33

Length*Width*Height	23*48.9*42.6 (mm)
Holder Diameter	22.2 (mm)
Connector	M5 Waterproof Connector
Ingress Protection Rating	IP67



With HUIYE, Connect to a Smarter Future



Scan to learn more
on our website



Scan to follow
our LinkedIn

Huiye IoT Technology Co., Ltd.

Web: www.huiye.com

Email: marketing@huiye.com

Version.2023.10